KYORENE® PRO GRAPHENE

00-887
SPECIFICATION SHEET

TOUCH SCREEN



ANSI/ISEA 105

A8

6 4

EN388

4X43F

ANSI/ISEA 138

2

CE UPF 100 OEKO TEX STANDARD 100 THERMAL REGULATION

SPECIFICATIONS:

- **Liner Materials:** 18g Gray Kyorene® Pro Graphene A8 Liner
- **Coating Materials:** Black HCT® MicroFoam Nitrile
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 00-887

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	22.69 lbs	22.91 lbs	26.43 lbs	27.75 lbs	29.74 lbs	34.14 lbs

PERFORMANCE LEVEL:

EN388: 4X43F

ABRASION	0	1	2	3	**4**	5	X
CUT	0	1	2	3	4	5	**X**
TEAR	0	1	2	3	**4**	5	X
PUNCTURE	0	1	2	**3**	4	5	X
CUT TDM TEST	A	B	C	D	E	**F**	

VERIFIED GRAPHENE® PRODUCER — THE GRAPHENE COUNCIL

ATTRIBUTES:

- 18g Gray Kyorene® Pro Graphene A8 Liner
- Black HCT® MicroFoam Nitrile Palm Coating

FEATURES:

- Silicone free
- Touchscreen compatible
- Back of hand TPV protection
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

APPLICATIONS:

- Oil & gas
- Mining
- Construction

CATEGORY:

- **Kyorene® Pro**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

KYORENE® PRO GRAPHENE

HCT Hybrid Coating Technology

ARMOR GUYS

www.armorguys.com / 10990 Wilshire Blvd. Suite 1410, Los Angeles CA 90024 / (310) 504-1380 / contact@armorguys.com